

# RAVENOL HTC HOT CLIMATE -15C Protect MB 325.0

**1,5 l**Vendor:  
**1410119-150****5 l**Vendor:  
**1410119-005****10 l**Vendor:  
**1410119-010****20 l**Vendor:  
**1410119-020****60 l**Vendor:  
**1410119-060****208 l**Vendor:  
**1410119-208****1 000 l**Vendor:  
**1410119-700**

**RAVENOL HTC Hybrid Tech. Coolant HOT CLIMATE -15°C** is a ready-to-use, prediluted with water, eco-friendly, 1,2- Ethanediol (monoethylene glycol) based amine and phosphate-free, all-season coolant with frost

and rust protection for Mercedes, BMW, Opel, Saab and General Motors engines. This product is formulated based on a proven inhibitor development by combining silicates with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL HTC Hybrid Tech. Coolant HOT CLIMATE -15°C** protects the cooling system from rust, frost, and in summer, from overheating.

## Application Note

**RAVENOL HTC Hybrid Tech. Coolant HOT CLIMATE -15°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL HTC Hybrid Tech. Coolant HOT CLIMATE -15°C** to radiator to fill line.

## Characteristics

- Excellent for use in cast iron or aluminium engines, or alloys of the two metals, and aluminium and copper alloy radiators
- Good reserve alkalinity
- Protection from corrosion and cavitation
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators

## Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
ASTM	D3306, D4340, D4985	
Complies with manufacturer's requirements	DTFR 29C100 (MB 325.0), DTFR 29D100 (MB 326.0), Ford ESE-M978 B4H-A, GM 1825M, GM 1899M, GM QL130100, MAN 324 Type NF, MB 325.0, MB 326.0, NATO S-759, Renault Glaceol RX Type D, SAE J 1034, VW TL 774-C	
Suitable for	DAF, GM SATURN, Jaguar, John Deere, Porsche, ROVER, SAAB, VW	
Density at 20 °C	1040 kg/m <sup>3</sup>	EN ISO 12185
Color	Blue	visual
pH - value at 20 °C	7,5	ASTM D1287
Freezing point	-15 °C	ASTM D1177

## Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
1,5 l	1410119-150-01-999	
5 l	1410119-005-01-999	
10 l	1410119-010-01-999	
20 l	1410119-020-01-999	
60 l	1410119-060-01-995	
208 l	1410119-208-01-995	