

# RAVENOL HJC HOT CLIMATE -15C Protect FL22

**1,5 l**Vendor:  
**1410124-150****5 l**Vendor:  
**1410124-005****10 l**Vendor:  
**1410124-010****20 l**Vendor:  
**1410124-020****60 l**Vendor:  
**1410124-060****208 l**Vendor:  
**1410124-208****1 000 l**Vendor:  
**1410124-700**

**RAVENOL HJC Hybrid Japan.Coolant HOT CLIMATE -15°C** is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without amines and silicates. This product is formulated based

on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL HJC Hybrid Japan.Coolant HOT CLIMATE -15°C** protects the cooling system from rust, frost, and in summer, from overheating.

## Application Note

**RAVENOL HJC Hybrid Japan.Coolant HOT CLIMATE -15°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL HJC Hybrid Japan.Coolant HOT CLIMATE -15°C** to radiator to fill line.

## Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

## Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Complies with manufacturer's requirements	Mazda FL22 Coolant, Subaru coolant 16218, Suzuki Longlife Coolant	
Density at 20 °C	1047 kg/m <sup>3</sup>	EN ISO 12185
Color	light green	visual
pH - value	7 - 8.5	ASTM D1287
Freezing point	-15 °C	ASTM D1177

## Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
1,5 l	1410124-150-01-999	
5 l	1410124-005-01-999	
10 l	1410124-010-01-999	
20 l	1410124-020-01-999	
60 l	1410124-060-01-999	
208 l	1410124-208-01-995	