

RAVENOL Super Truck 40

Вискозност: 40W

Минерално уље



1 л

Чланак:
1123725-001



5 л

Чланак:
1123725-005



10 л

Чланак:
1123725-010



20 л

Чланак:
1123725-020



20 л, ecobox

Чланак:
1123725-B20



60 л

Чланак:
1123725-060



208 л

Чланак:
1123725-208



1 000 л

Чланак:
1123725-700

RAVENOL Super Truck SAE 40 is a top-quality product with high safety reserves.

Application Note

RAVENOL Super Truck SAE 40 is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Please follow engine manufacturer's recommendations.

Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- Good cold start characteristics
- Best corrosion protection
- High safety reserves even with boundary lubrication conditions
- Suitable for catalysts

Карактеристике

Име	Значење	Ревизија
API	CF-4, SG	
ACEA	B4, E2	
Испуњава захтеве	Allison C-4, Caterpillar TO-2, Deutz DQC I-02, MAN 270, MB 228.0, MB 235.12, MIL-L-2104 D, MTU Type 1, ZF TE-ML 02H, ZF TE-ML 04A, ZF TE-ML 04B	
Густина на 20°C	883 г/цм ³	EN ISO 12185
Боја	Бровн	visual
Вискозност на 100°C	14.3 мм ² /с	DIN 51562-1
Вискозност на 40°C	131.5 мм ² /с	DIN 51562-1
Индекс вискозности VI	108	DIN ISO 2909
Тачка стињавања	-21 °Ц	DIN ISO 3016
Температура паљења	246 °Ц	DIN EN ISO 2592

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1123725-001-06-999	
5 л	1123725-005-01-400 1123725-005-01-999	
10 л	1123725-010-01-999	
20 л	1123725-020-01-400 1123725-020-01-999	
208 л	1123725-208-01-999	