

# RAVENOL MARINE 1640 40 TBN16

**Вискозност: 40W**

**Минерално уље**



**1 л**

Чланак:  
**1163021-001**  
Чланак:  
1163021-001-01-999



**4 л**

Чланак:  
**1163021-004**  
Чланак:  
1163021-004-01-999



**10 л**

Чланак:  
**1163021-010**



**20 л**

Чланак:  
**1163021-020**  
Чланак:  
1163021-020-01-999



**20 л, esobox**

Чланак:  
**1163021-B20**



**60 л**

Чланак:  
**1163021-060**  
Чланак:  
1163021-060-01-999



**208 л**

Чланак:  
**1163021-208**  
Чланак:  
1163021-208-01-999



**1 000 л**

Чланак:  
**1163021-700**

**RAVENOL MARINE 1640 SAE 40 TBN16** is made from high quality solvent refined basic oils with a special multi functional additivation for the demands of a navy oil for the use of navy diesel engines and for the lubrication of gear transfers in aggregates used on boats.

## Application Note

**RAVENOL MARINE 1640 SAE 40 TBN16** is used as a lubrication oil in quickly running and so-called « mediumspeed » navy diesel engines, perhaps with turbo charging and when using distilled fuels with a sulfur content upto 1,8 %.

**RAVENOL MARINE 1640 SAE 40 TBN16** can also be used for the lubrication of gear transfers in aggregates used on boats.

## Characteristics

- a very good oxidation resistance
- a stable viscosity index
- excellent dispersant and detergent characteristics
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

## Карактеристике

| Име                      | Значење                   | Ревизија        |
|--------------------------|---------------------------|-----------------|
| API                      | CF                        |                 |
| Испуњава захтеве         | DEF 91-22/2, MIL-L-2104 C |                 |
| Испуњава спецификације   | SAE 40                    |                 |
| Густина на 20°C          | 893 г/цм <sup>3</sup>     | EN ISO 12185    |
| Боја                     | Бровн                     | visual          |
| Вискозност на 100°C      | 14.5 мм <sup>2</sup> /с   | DIN 51562-1     |
| Вискозност на 40°C       | 146 мм <sup>2</sup> /с    | DIN 51562-1     |
| Индекс вискозности VI    | 97                        | DIN ISO 2909    |
| Тачка стињавања          | -18 °Ц                    | DIN ISO 3016    |
| Температура паљења       | 268 °Ц                    | DIN EN ISO 2592 |
| Основни број             | 17.4 мгКОХ/г              | ASTM D2896      |
| Садржај сулфатног пепела | 2.21 %wt.                 | DIN 51575       |
| Ход мотора               | 4Т                        |                 |

## Укинуто паковање

| Паковање | Чланак             | Баркод |
|----------|--------------------|--------|
| 1 л      | 1163021-001-06-999 |        |
| 10 л     | 1163021-010-01-999 |        |