

RAVENOL MARINEOIL PETROL 15W-40

Вискозност: 15W-40

Минерално уље



1 л

Чланак:
1163200-001



4 л

Чланак:
1163200-004



10 л

Чланак:
1163200-010



20 л

Чланак:
1163200-020



20 л, eco box

Чланак:
1163200-B20



60 л

Чланак:
1163200-060



208 л

Чланак:
1163200-208

RAVENOL MARINEOIL PETROL SAE 15W-40 is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

Application Note

RAVENOL MARINEOIL PETROL SAE 15W-40 is tried and tested for aggregates specifying:

Specification: API SL

Recommendations: VOLVO Penta AB, Mercruiser, Yanmar, Kohler

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Карактеристике

Име	Значење	Ревизија
API	SL	
Испуњава захтеве	Volvo Penta AB	
Погодан за	Kohler, Mercruiser, Yanmar	
Густина на 20°C	879.5 г/цм³	EN ISO 12185
Боја	Плави	visual
Вискозност на 100°C	15 мм²/с	DIN 51562-1
Вискозност на 40°C	115.7 мм²/с	DIN 51562-1
Индекс вискозности VI	134	DIN ISO 2909
Тачка стињавања	-36 °Ц	DIN ISO 3016
Температура паљења	238 °Ц	DIN EN ISO 2592
Основни број	10.5 мгКОХ/г	ASTM D2896

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1163200-001-01-999	
4 л	1163200-004-01-999	
10 л	1163200-010-01-999	
20 л	1163200-020-01-999	
60 л	1163200-060-01-999	
208 л	1163200-208-01-999	