

RAVENOL Motobike 4-T Mineral 20W-40

Вискозност: 20W-40**Минерално уље****1 л**

Чланак:
1173123-001
Чланак:
1173123-001-01-999

**4 л**

Чланак:
1173123-004
Чланак:
1173123-004-01-999

**10 л**

Чланак:
1173123-010
Чланак:
1173123-010-01-999

**20 л**

Чланак:
1173123-020
Чланак:
1173123-020-01-999

**20 л, еsobox**

Чланак:
1173123-B20

**60 л**

Чланак:
1173123-060
Чланак:
1173123-060-01-999

**208 л**

Чланак:
1173123-208
Чланак:
1173123-208-01-999

RAVENOL Motobike 4-T Mineral 20W-40 has an excellent lubricating film adhesive capacity and very good shear stability as well as an excellent cleaning power and a high aging resistance.

Application Note

RAVENOL Motobike 4-T Mineral 20W-40 is suitable as an engine oil for all motorbikes in case the specification SAE 20W-40 JASO MA/MA2 is requested.

Characteristics

- a very good shear stability
- very good cold start characteristics
- a high oxidation stability
- prevention of black sludge accumulation
- an excellent viscosity temperature behaviour
- suitable for catalysts
- convincing detergent and dispersant characteristics
- high safety reserves even under boundary lubrication conditions

Карактеристике

Име	Значење	Ревизија
API	SN	
JASO	MA2	
JASO T904 DFI	2.04	JASO T904
JASO T904 SFI	1.69	JASO T904
JASO T904 STI	1.98	JASO T904
Погодан за	Aprilia, BMW, Ducati, Honda, Kawasaki, Moto-Guzzi, Suzuki, Triumph, Yamaha	
Густина на 20°C	872.4 г/цм ³	EN ISO 12185
Боја	Жуто-браон	visual
Вискозност на 100°C	14.24 мм ² /с	DIN 51562-1
Вискозност на 40°C	125.45 мм ² /с	DIN 51562-1
Индекс вискозности VI	113	DIN ISO 2909
Ниска температура вискозитета (CCS) на -25°C	7830 мПа*с	ASTM D5293
Тачка стињавања	-27 °Ц	DIN ISO 3016
Волатилност NOACK	2.7 %	ASTM D5800
Температура паљења	272 °Ц	DIN EN ISO 2592
Основни број	7.7 мгКОХ/г	ASTM D2896
Садржај сулфатног пепела	0.85 %wt.	DIN 51575
Ход мотора	4Т	