

RAVENOL LKW ATF Synthetik

Синтетички



4 л

Чланак:
1211104-004



10 л

Чланак:
1211104-010
Чланак:
1211104-010-01-999



20 л

Чланак:
1211104-020
Чланак:
1211104-020-01-999
Баркод:
4014835736825



20 л, есобох

Чланак:
1211104-B20



60 л

Чланак:
1211104-060



60 л, штампано буре

Чланак:
1211104-D60



208 л

Чланак:
1211104-208
Чланак:
1211104-208-01-999
Баркод:
4014835736887



208 л, штампано буре

Чланак:
1211104-D28
Чланак:
1211104-D28-01-888
Баркод:
4014835736801



1 000 л

Чланак:

1211104-700

RAVENOL LKW ATF Synthetik allows oil change intervals to be extended even under severe operating conditions. A new type of additive technology allowed ultimate performance to be achieved with respect to ideal and constant friction characteristics, excellent shearing stability, and fluidity at low temperatures, steady wear protection and outstanding oxidation stability.

Application Note

RAVENOL LKW ATF Synthetik was developed for use in automatic transmissions in motor vehicles as well as torque converter and power-shift transmissions with the indicated specifications.

Characteristics

- reliable protection from wear, sludge, adhesion and corrosion
- excellent, highly shearing stable viscosity-temperature properties
- no problems in very low and very high temperatures
- a thermally extremely high load capacity
- non-foaming even in extreme conditions
- neutral behavior towards sealing materials

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Карактеристике

Име	Значење	Ревизија
Испуњава захтеве	Allison TES-295, Allison TES-468, Caterpillar 6-speed CX31, Caterpillar 8-speed Super-Heavy-Duty CX35, DTFR 13C180 (MB 236.91), MAN 339 Type Z4, MB 236.91, Renk Doromat, Voith H55.63353x (G607), Voith H55.63363x (G1363), ZF TE-ML 14E, ZF TE-ML 16N	
Густина на 20°C	834 г/цм³	EN ISO 12185
Боја	Црвени	visual
Вискозност на 100°C	7.5 мм²/с	DIN 51562-1
Вискозност на 40°C	32 мм²/с	DIN 51562-1
Индекс вискозности VI	191	DIN ISO 2909
Тачка стињавања	-54 °Ц	DIN ISO 3016
Температура паљења	226 °Ц	DIN EN ISO 2592

Аналоги OEM

General Motors

12378515, 88900701

Mercedes-Benz

A001989730309, A001989730312

Укинуто паковање

Паковање	Чланак	Баркод
4 л	1211104-004-01-999	
10 л	1211104-010-01-999	
20 л	1211104-020-01-999	
20 л, еcobox	1211104-B20-01-888	
60 л	1211104-060-01-999	
208 л	1211104-208-01-999	