

# RAVENOL Truck MTF-50

Потпуно синтетички



**1 л**

Чланак:  
**1221106-001**  
Чланак:  
1221106-001-01-999



**4 л**

Чланак:  
**1221106-004**  
Чланак:  
1221106-004-01-999



**10 л**

Чланак:  
**1221106-010**



**20 л**

Чланак:  
**1221106-020**  
Чланак:  
1221106-020-01-999



**60 л**

Чланак:  
**1221106-060**  
Чланак:  
1221106-060-01-999



**208 л**

Чланак:  
**1221106-208**  
Чланак:  
1221106-208-01-999

**RAVENOL Truck MTF-50** is based on synthetic base oils and special additives matched to them. Thus, the extended requirements of Eaton axle and transmission divisions are fulfilled.

**RAVENOL Truck MTF-50** is ideally suited for severe operating conditions and extended oil change intervals.

## Application Note

**RAVENOL Truck MTF-50** is recommended for extended drain and severe service in heavy duty (class 6, 7, and 8) manual transmissions requiring a non-EP lubricant.

## Characteristics

- Excellent thermal stability.
- Strong protection against rust, corrosion and foaming.
- A very low pour point.
- Excellent EP properties.
- A good switching behavior at low temperatures.
- An extended service life.
- Fuel savings.

## Карактеристике

| Име                                      | Значење                                                                                                                 | Ревизија        |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------|
| API                                      | MT-1                                                                                                                    |                 |
| Испуњава захтеве                         | Arvin Meritor 0-81, Eaton PS-164 Rev. 7, International Harvester TMS-6816, Mack TO-A Plus, ZF FreedomLine, ZF TE-ML 02L |                 |
| Густина на 20°C                          | 857 г/цм³                                                                                                               | EN ISO 12185    |
| Боја                                     | Бровн                                                                                                                   | visual          |
| Вискозност на 100°C                      | 17.5 мм²/с                                                                                                              | DIN 51562-1     |
| Вискозност на 40°C                       | 132 мм²/с                                                                                                               | DIN 51562-1     |
| Индекс вискозности VI                    | 146                                                                                                                     | DIN ISO 2909    |
| Вискозност, Брукфилд на -26°C            | 16.900 мПа*с                                                                                                            | ASTM D2983      |
| Тачка стињавања                          | -45 °Ц                                                                                                                  | DIN ISO 3016    |
| Температура паљења                       | 221 °Ц                                                                                                                  | DIN EN ISO 2592 |
| Испитивање корозије бакра, на 121°C / 3х | 1a                                                                                                                      | ASTM D130       |

## Укинуто паковање

| Паковање | Чланак             | Баркод |
|----------|--------------------|--------|
| 10 л     | 1221106-010-01-999 |        |