

RAVENOL STOU 15W-40

Вискозност: 15W-40

Минерално уље



5 л

Чланак:
1310113-005
Чланак:
1310113-005-01-999



10 л

Чланак:
1310113-010
Чланак:
1310113-010-01-999
Баркод:
W24001055



20 л

Чланак:
1310113-020
Чланак:
1310113-020-01-999
Баркод:
4014835740020



20 л, есобох

Чланак:
1310113-B20



60 л

Чланак:
1310113-060
Чланак:
1310113-060-01-999



208 л

Чланак:
1310113-208
Чланак:
1310113-208-01-999



1 000 л

Чланак:
1310113-700

RAVENOL STOU SAE 15W-40 is equal to use in engines, transmissions and hydraulic systems of modern tractors. Top-grade solvent refined base oils and special synthetic based additives ensure trouble-free operation of all units in all seasons.

Application Note

RAVENOL STOU SAE 15W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 15W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- Excellent extreme pressure properties
- A high and stable viscosity index

Карактеристике

Име	Значење	Ревизија
API	CE, CF-4, GL-4, SF	
ACEA	E1	
Испуњава захтеве	Allison C-4, Caterpillar TO-2, Ford ESN-M2C 134-D, Ford ESN-M2C 159-C, Ford ESN-M2C 86-A, John Deere J27, MB 227.1, Massey Ferguson CMS M1143, Massey Ferguson CMS M1144, New Holland 410B, New Holland 420A, ZF TE-ML 06B, ZF TE-ML 07B	
Испуњава спецификације	CCMC D4, CCMC G2	
Густина на 20°C	865 г/цм³	EN ISO 12185
Боја	Бровн	visual
Вискозност на 100°C	13.3 мм²/с	DIN 51562-1
Вискозност на 40°C	94.2 мм²/с	DIN 51562-1
Индекс вискозности VI	141	DIN ISO 2909
Тачка стињавања	-36 °Ц	DIN ISO 3016
Температура паљења	228 °Ц	DIN EN ISO 2592
Основни број	12.8 мгКОХ/г	ASTM D2896

Аналоги OEM

Volvo

1161930, 1161908