

RAVENOL Frostlube F 22

Минерално уље



1 л

Чланак:
1323351-010



208 л

Чланак:
1323351-208

RAVENOL Frostlube F 22 is a high quality, anti-wear hydraulic oil with a very high viscosity index, good shear stability and excellent low-temperature properties.

Application Note

RAVENOL Frostlube F 22 is excellently suitable for application in extremely low temperatures, e.g. equipment in refrigerated warehouses or mobile facilities, which are used outdoors under extreme winter conditions.

RAVENOL Frostlube F 22 is specifically formulated so that a consistent viscosity is extensively given even in the case of extremely varying temperatures.

RAVENOL Frostlube F 22 is a shear stable, high quality hydraulic oil and therefore, suitable for application under extreme hydraulic conditions without risk for the system. If the oil temperature is permanently above 80°C, the hydraulic system should be pressurized to minimize oil loss due to evaporation.

Characteristics

- An extremely high viscosity index so that the good lubrication properties and the protection in the event of minimal viscosity alterations are ensured by a wide temperature range.
- A low pour point; therefore, application at extremely low temperatures is permitted without the risk of freezing.
- An extremely good resistance to oxidation and a very good shear stability; therefore, longer service life of the oil under the usually extreme application conditions.
- Protection of the hydraulic system against corrosive influences.

- Anti-wear effect.
- Load bearing capability.
- Longer service life of the oil.

Карактеристике

| Име | Значење | Ревизија |
|------------------------|-------------------------|-----------------|
| Испуњава спецификације | ISO 6743-4 HV | |
| Густина на 20°C | 837 г/цм ³ | EN ISO 12185 |
| Боја | Зелен | visual |
| Вискозност на 100°C | 7.3 мм ² /с | DIN 51562-1 |
| Вискозност на 40°C | 25.4 мм ² /с | DIN 51562-1 |
| Индекс вискозности VI | 274 | DIN ISO 2909 |
| Тачка стињавања | -63 °Ц | DIN ISO 3016 |
| Температура паљења | 156 °Ц | DIN EN ISO 2592 |

Укинуто паковање

| Паковање | Чланак | Баркод |
|----------|--------------------|--------|
| 1 л | 1323351-010-01-999 | |
| 208 л | 1323351-208-01-999 | |