

RAVENOL Kompessorenoel VDL 220

Вискозност: 220

Минерално уље



20 l

Чланак:
1330102-020



60 l

Чланак:
1330102-060
Чланак:
1330102-060-01-999



208 l

Чланак:
1330102-208
Чланак:
1330102-208-01-999

RAVENOL Kompessorenoel VDL 220 has a good adhesion, is water repellent and wear reducing. As many compressors operate at high temperatures, the oil should have good aging resistance at very low residue formation.

RAVENOL Kompessorenoel VDL 220 provides a secure lubrication not only in the upper temperature range, also in the cold state of the compressor to achieve a reduction of wear. By selected and coordinated additive composition the tendency to coking and the formation of flammable residues is minimized.

Application Note

RAVENOL Kompessorenoel VDL 220 can be used in stationary and mobile compressors with discharge temperatures up to 220°C.

RAVENOL Kompessorenoel VDL 220 can also be used for lubrication of engines and diesel engines where the manufacturer does not stipulate any HD motor oil.

Exceeds the requirements for VBL- and VCL-oils.

Characteristics

- Excellent aging resistance
- Best wear protection
- Excellent viscosity-temperature behavior
- Very good cold starting properties
- Low coking tendency

Карактеристике

Име	Значење	Ревизија
Испуњава спецификације	DIN 51506 VDL	
Погодан за	ALUP, Atlas Copco Kompressor, CompAir, FIAC, FINI, KAESER, VW	
Густина на 20°C	893 g/cm ³	EN ISO 12185
Боја	Жуто-браон	visual
Вискозност на 100°C	18.8 mm ² /s	DIN 51562-1
Вискозност на 40°C	226.5 mm ² /s	DIN 51562-1
Индекс вискозности VI	93	DIN ISO 2909
Тачка стињавања	-9 °C	DIN ISO 3016
Температура паљења	276 °C	DIN EN ISO 2592
Препоруке	ALUP, Atlas Copco Kompressor, Audi, CompAir, FIAC, FINI, KAESER	

Укинуто паковање

Паковање	Чланак	Баркод
20 l	1330102-020-01-999	