

RAVENOL Bettbahnöl 32

Вискозност: 32W**Минерално уље****208 л**

Чланак:

1350374-208

Чланак:

1350374-208-01-999

RAVENOL Bettbahnoel 32 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 32 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 32 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Note

RAVENOL Bettbahnoel 32 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Wear protection and pressure absorption capacity
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Карактеристике

Име	Значење	Ревизија
Испуњава захтеве	Eaton Vickers M-2950-S, Fives Cincinnati P-53, GM LS-2, GM LW-03-1-04	
Испуњава спецификације	AFNOR E 60-203 HG, AFNOR E 60-203 L-G, DIN 51502 CGLP, DIN 51517-3, DIN 51524-2, GB 11118.1-94 L-HG, GB 11118.1-94 L-HM, ISO 11158 HG, ISO 11158 HM, ISO 19378 GA, ISO 19378 GB, ISO 6743-13 GA, ISO 6743-13 GB, ISO 6743-6 CKC, SAE MS 1007 Type E, SH/T 0361-98 L-G	
Густина на 20°C	854 г/цм ³	EN ISO 12185
Боја	Жута	visual
Вискозност на 100°C	5.75 мм ² /с	DIN 51562-1
Вискозност на 40°C	31.9 мм ² /с	DIN 51562-1
Индекс вискозности VI	123	DIN ISO 2909
Тачка стињавања	-33 °C	DIN ISO 3016
Температура паљења	216 °C	DIN EN ISO 2592