

RAVENOL Bettbahnöl 220

Вискозност: 220**Минерално уље****20 л**

Чланак:
1350378-020
Чланак:
1350378-020-01-999
Баркод:
4014835763623

**60 л**

Чланак:
1350378-060

**208 л**

Чланак:
1350378-208
Чланак:
1350378-208-01-999

RAVENOL Bettbahnoel 220 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 220 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 220 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Note

RAVENOL Bettbahnoel 220 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Карактеристике

Име	Значење	Ревизија
Испуњава спецификације	DIN 51502 CGLP, DIN 51517-3, DIN 51524-2	
Густина на 20°C	890 г/цм ³	EN ISO 12185
Боја	Жута	visual
Вискозност на 100°C	18.7 мм ² /с	DIN 51562-1
Вискозност на 40°C	216.7 мм ² /с	DIN 51562-1
Индекс вискозности VI	96	DIN ISO 2909
Тачка стињавања	-15 °C	DIN ISO 3016
Температура паљења	250 °C	DIN EN ISO 2592